



CONNECTORS AND CABLES

/ for installing NMEA 2000 networks

Connectors





9057*

NMEA 2000 Elbow Adaptor



Brown

Green

- 0V

- 12V

- 0V

- 12V

- Drain

Connectors 3

Our range of connectors include ...

V

9026

9028





Micro Trunk to Micro Drop Tee Adaptor

Micro Male Terminator


9029

9058

9059 / 9060







Micro Female Terminator

Micro Dual Micro Tee Adaptor

Female / Male Blanking Plugs

9061

9062

9063







Micro Bulkhead Feedthrough

NMEA 2000 Field Installable Screw In (Metal Nut)

Female connector

NMEA 2000 Field Installable Screw In (Metal Nut)

Male connector

Cables



9030 (0.5 metre)

Micro Trunk Drop Cable

9031 (1 metre)

Micro Trunk Drop Cable

9032 (2 metres)

Micro Trunk Drop Cable

9035 (5 metres)

Micro Trunk Drop Cable

9040 (10 metres)

Micro Trunk Drop Cable

9049* (0.5 metre)

Micro Trunk / 90° Drop Cable (Female / Male)

9050* (1.0 metre)

Micro Trunk / 90° Drop Cable (Male / Female)

Honda / Tohatsu Outboard engine to NMEA 2000® cable





FRONT

9052 (6 metres)

This cable is compatible with both Honda and Tohatsu Outboard Engines

Cables 5



9001

Simrad Yellow Connector to M12 Male D-Code 4pin plastic 2m Cable



9002

M12 4 pin D-Code Female to RJ45 IP67 cap - 1m Cable




9003

Raymarine to M12D 4pin Seakeeper -3m Cable

NMEA 2000® connection diagram



NMEA 2000® cables





Male

Connectors



Pin 1: Shield

Pin 2: NET-S (power supply possitive +V)

Pin 3: NET-C (power supply common -V)

Pin 4: NET-H (CAN-H)
Pin 5: NET-L (CAN-L)



Telephone:

Europe & Worldwide +44 (0) 1202 973 023 USA & Canada +00 1941 538 7775

Email:

International Sales Team – info@veethree.com USA Sales Team – sales@veethree.com

