NON-SWIVELING CONNECTORS

4GNS Connections



THE 4GNS CONNECTOR REDEFINING CONNECTIONS

The new 4GNS connector will be redefining connections on key positions. It's the answer to yachts increasing in size and complexity asking for more safety, plug-and-play installation and easy to service.



USED ON:

Genoa sheets Stay sail sheets Main halyard

WHY THE NEED OF A SEPERABLE CONNECTOR?

Because yachts increasing in size, and therewith the workloads and line sizes also, servicing connectors of a sheet is much more difficult. With the 4GNS connector it's possible to detach only the connector with letting the sheet in position.

The 4GNS connector is made for sheets from 24 millimeter.

For installation, divide the two connector-body pieces and place the spliced eye over the loop and onto the groove in the aluminum body. Now, re-attach the second half en firmly tighten using the tools included.



A SOLID SOLUTION WITH APPROVED FIBER CERTIFICATE

We consider safety on board is very important. Therefore, the connectors are supplied with a certificate issued by a ISO9001-VCA-EKH certified company. This certificate guarantees the maximum workloads.

Adding the certificate to a yachts management system, guarantees close record keeping and the approval of marine surveyors and insurance companies.









MEASUREMENT SHEET





Part	line Ø	T	Ø*	W	Ld	Wt (g)	MWL (kg)
24-14 4G-NS	24	150	60	77	14	614	18.000
30-14 4G-NS	30	150	60	73	14	720	18.000
24-16 4G-NS	24	150	67	81	16	720	28.000
30-16 4G-NS	30	180	67	91	16	1.040	28.000
34-16 4G-NS	34	180	67	95	16	1.100	28.000
32-18 4G-NS	32	200	71	98	18	1.466	35.000
34-18 4G-NS	34	200	71	101	18	1.490	35.000
35-20 4G-NS	35	200	75	105	20	1.510	45.000