

PRODUCT DATA SHEET

DULON 1&2

2-component polish- & waxsystem
Longlasting high gloss armour protection

DESCRIPTION

Revolutionary 2-component polish- & wax system which creates a unique and impermeable molecular shield on hard surfaces like gel coat, painted steel/wood and stainless steel. DULON 1&2 gives a long-lasting high gloss armor protection, is both easy to apply and economical.

HOW TO APPLY

PRETREATMENT (if required)

Use DULON BOATBOTTOM CLEAN 24 to remove algae, barnacles and weed.

Use DULON HULL & WATERLINE CLEAN 22 to remove scale and brownish/yellow stains.

Use DULON POLY POLISH (strong, medium or fine) to restore weathered surfaces also to remove dull patches, scratches, persistent stains and streaks.

DULONATING

Use PREDULON 00 to remove surface dirt, grease, oil, old wax and silicon traces.

Apply DULON 1 using a damp cloth or sponge and leave it to dry until white haze appears.

Do not rub off!

Apply DULON 2 using a damp cloth or sponge and leave it to dry until white haze appears.

Buff using a dry cloth or lamb's wool pad and the 2-component high gloss protection system has been activated.

In the following weeks clean/wash the dulonated surface at regular intervals using DULON PREMIUM SHAMPOO 03.

A set of DULON 1&2 (500 ml) will treat 10-15 meter vessel and gives 365 days high gloss armor protection.

