

Nozzle Bulb



Features:

- Unique patented design with high performance for cooling effect and low consumption of water.
- Easy to install and test for both commissioning and maintenance.
- 603 nozzles are supplied with a star lock for easy mounting.
- 603 nozzle body can be supplied as threaded M20 with optional nut.
- Nozzle tools and spares are available for maintenance.
- Working pressure – 100 bar.
- Ultra Fog is the only company that can test the nozzle without breaking the frangible glass bulb.

Technical Data:

Nozzle Type	Spacing (C-C)	Ceiling Height	Covering Area	Mounting	K Value (K=)
603-13 -B	3,0m	2,5m	9m ²	Ceiling	1,3
603-260-061-B	5,3m	2,5m	28m ²	Ceiling	3,21
603-300-061-B	5,3m	5,0m	28m ²	Ceiling	3,61
603-08 -B	centre in the room	2,5m	12m ² (cabin)	Ceiling (cent)	0,8
603-200-061-B	centre in the room	2,5m	20m ² (cabin)	Ceiling (cent)	2,61
603-260-061-B	centre in the room	2,5m	48m ² (cabin)	Ceiling (cent)	3,21
603-093-B-W	centre in the room	2,5m	12m ² (cabin)	Wall (cent) *	0,93
603-050-260-B-W	centre in the room	2,5m	25m ² (cabin)	Wall (cent) *	3,1
603-19 -B	5,3m	2,5m	Corridor ≤1,5m	Ceiling	1,9
603-100-035-B-W	4,0m	2,5m	Corridor ≤1,5m	Wall (cent) *	1,35
603-13 -B	2,25m	2,5m	Store	Ceiling	1,3

* The wall nozzles must be mounted ~15cm from the ceiling.