






# ...THE MULTIFLAP — 100% CARBON FIBRE LIGHTWEIGHT FOR HEAVYWEIGHT

Extremely light weight yet with maximum load capacity are just two demands made on yachting equipment. As part of multiplex's commitment to pursuing the demand for cutting-edge manufacturing techniques and innovative materials, it has developed the multi-flap — a gangway manufactured from a 100% carbon fibre base. This provides a wide range of benefits exclusive to the use of this special material. The multiflap is light, stable and resistant to deformation. It is also weather-proof, which means that neither wind nor seawater can cause any harm. With a weight of 4.4 kg per metre and a quick, simple fixing system, it can be mounted and dismounted by a single person. The practical hinge system keeps storage space to a minimum.

Multiplex gangways are manufactured with firstclass craftmanship, in line with LR Lloyds Register guidelines.







- · SELECT THE LENGTH AND WIDTH OF YOUR GANGWAY
- · SELECT THE FINISH AND COLOUR OF YOUR CHOICE
- · CHOOSE BETWEEN ANTI-SLIP AND NATURAL TEAK WOOD SURFACES
- · SELECT THE MATERIAL AND COLOUR OF YOUR STANCHIONS — STAINLESS STEEL OR EXTRA LIGHT, STURDY CARBON FIBRE

# YOUR OWN MULTIFLAP

TOTAL LENGTH: UP TO 9,000 MM
TOTAL WIDTH: UP TO 900 MM

FOLDABLE OR NON-FOLDABLE

COLOUR OF YOUR CHOICE

# **WALKING AREA**

- · TEAK COVERING
- · ANTI SLIP SURFACE

#### HANDRAIL

- · CARBON STANCHIONS WITH ROPE
- · STAINLESS STEEL STANCHIONS WITH ROPE
- · TEAK HANDRAIL WITH CARBON STANCHIONS
- · CARBON HANDRAIL WITH CARBON
- · STANCHIONS

#### STORAGE BAG

COLOUR OF YOUR CHOICE

LED LIGHTING SYSTEM

### **VESSEL NAME**


IN FONT, SIZE AND COLOUR OF YOUR CHOICE


# LLOYDS CERTIFICATE

APPROVED LLOYDS REGISTER LOAD CERTIFICATE

### HINGES

HIGH QUALITY HINGES ARE LOCATED IN THE MIDDLE OF THE MULTIFLAP. WITH THE CARBON FIBRE RECEPTACLES AND AN AXLE MADE OF A SPECIAL TITANIUM ALLOY THAT ENSURES A LOAD BEARING CAPACITY TO 1000 KG, THE GANGWAY CAN BE FOLDED IN HALF, SAVING STOWAGE SPACE AND ENSURING EASY HANDLING ON BOARD.






A) THE HOISTING SYSTEM SUPPORTS
YOU WHEN MOUNTING AND
DISMOUNTING THE MULTIFLAP.

B) THE JUMPER SYSTEM
ENSURES STABLE POSITIONING
OF THE GANGWAY. IT STABILISES
THE MULTIFLAP AGAINST THE
EFFECT OF WAVES OR OTHER
LATERAL MOVEMENTS.

PRODUCTION PERIOD: 8 WEEKS SAFE WORKING LOAD: 250 KG ESTIMATE WEIGHT: 4.4 KG PER METRE



# **DETAILS OF YOUR MULTIFLAP-SYSTEM!**



**ANTI-SLIP SURFACE** 



**TEAK SURFACE** 




**TEAK HANDRAIL** 



**CARBON HANDRAIL** 




CARBON STANCHIONS WITH ROPE
STAINLESS STEEL STANCHION WITH ROPE



LED ILLUMINATION



**BOARDING RAMP** 



STORAGE BAG



ASK ABOUT OUR OTHER CUSTOMISED SOLUTIONS!

