

LED Flashing beacon SHARK-S



LED Flashing beacon ultra-compact, 79mm high.

Source of light composed of a single crown with 9 LEDs;
Available in 12V version or in Multivoltage version (12/24V);
Available in blue and in amber colour;
Polycarbonate U.V. stabilized dome, Aluminium body,
Heatsink, IP66 (available also IP68).

With the following functions:

- Flashing
- Stationary Light
- Flashing Synchronism (2 devices) available on Ip68 version,
- Failure Control available in the Multivoltage version, available on IP68 version,





Homologations

Reg.65 ECE-ONU

Reg.10 ECE-ONU

Voltage	Consumption		Working Temperature	Weight	IP index
	Average	Max.			
12V	0,8A	2,5A	-20° C / +50° C	0,64Kg	IP66 / IP68
24V	0,5A	1,5A			

Code	Colour	Mounting	Crown	LED	Voltage
SHARK9SB12V		Fisso 3-bolt		9	12V
SHARK9SB12V.DP		DIN Pole		9	12V
SHARK9SBMV		Magnetico		9	Multi 12/24V
SHARK9SBMV.DP		DIN Pole		9	Multi 12/24V
SHARK9SA12V		Fisso 3-bolt		9	12V
SHARK9SA12V.DP		DIN Pole		9	12V
SHARK9SA12V.M		Magnetico 110Km/h		9	12V
SHARK9SAMV		Fisso 3-bolt		9	Multi 12/24V
SHARK9SAMV.DP		DIN Pole		9	Multi 12/24V



*190mm montaggio DIN Pole
90mm montaggio Magnetico



Fisso 3-bolt	8pz	12pz
DIN Pole	4pz	6pz
Magnetico	8pz	12pz

