

# LED Flashing beacon SHARK-H



## LED Flashing beacon ultra-compact, 105mm high.

Source of light composed of a single crown with 9 LEDs or a double crown 6+6 LEDs;  
Available in 12V version or in Multivoltage version (12/24V); Available in blue and in amber colour;  
Polycarbonate U.V. stabilized dome, Aluminium body, Heatsink, IP66 (available also IP68).

With the following functions:

- Flashing
- Stationary Light
- Flashing Synchronism (2 devices) available on IP68 version,
- Failure Control available in the Multivoltage version, available on IP68 version,



## Homologations

Reg.65 ECE-ONU

Reg.10 ECE-ONU



Voltage	Consumption		Working Temperature	Weight	IP index
	Average	Max.			
12V	0,8A	2,5A	-20° C / +50° C	0,64Kg	IP66 / IP68
24V	0,5A	1,5A			

Code	Colour	Mounting	Crown	LED	Voltage
SHARK9HB12V	●	Fisso 3-bolt	☐	9	12V
SHARK9HB12V.DP	●	DIN Pole	☐	9	12V
SHARK9HBMV	●	Fisso 3-bolt	☐	9	Multi 12/24V
SHARK9HBMV.DP	●	DIN Pole	☐	9	Multi 12/24V
SHARK9HA12V	●	Fisso 3-bolt	☐	9	12V
SHARK9HA12V.DP	●	DIN Pole	☐	9	12V
SHARK9HA12V.M	●	Magnetico 110Km/h	☐	9	12V
SHARK9HAMV	●	Fisso 3-bolt	☐	9	Multi 12/24V
SHARK9HAMV.DP	●	DIN Pole	☐	9	Multi 12/24V
SHARK66HB12V	●	Fisso 3-bolt	☐	6+6	12V
SHARK66HB12V.DP	●	DIN Pole	☐	6+6	12V
SHARK66HBMV	●	Fisso 3-bolt	☐	6+6	Multi 12/24V
SHARK66HAMV.DP	●	DIN Pole	☐	6+6	Multi 12/24V
SHARK66HA12V	●	Fisso 3-bolt	☐	6+6	12V
SHARK66HA12V.DP	●	DIN Pole	☐	6+6	12V
SHARK66HA12V.M	●	Magnetico 110Km/h	☐	6+6	12V
SHARK66HAMV	●	Fisso 3-bolt	☐	6+6	Multi 12/24V
SHARK66HAMV.DP	●	DIN Pole	☐	6+6	Multi 12/24V

+ INFO: WWW.INTAV-EUROPE.COM



ISO	8pz	12pz
DIN Pole	4pz	6pz
Magn.	8pz	12pz



\*216mm hamp mounting  
116mm magnetic mounting