

KETOS 81/2K



The Dry/Wet-vaccum KETOS satisfies through the newest technology, enormous performance ability, and a large container volume of 80 litres.

Suggested Use

Ideal for contractors, facilities and maintenance services and the food service industry.

The KETOS, with its wear-resistant plastic container, is an extremely high-performance, modern and commercial professional vacuum, developed for heavy daily use. With 300 mbar pressure and a 70 litres/sec. volume flow per vacuum motor, the KETOS provides enough power for every situation. Along with the stable container, the KETOS is equipped with a robust undercarriage, metal swivel casters and large rubber-coated wheels.

The reliable, patent-pending Cyclone Water Separation System has been integrated into the new product line and assures optimal water intake. Through the swirling motion at the intake, spray water is segregated upon contact with the container wall.

Additional filter materials are no longer needed. Further more, the KETOS is equipped with a blower function on the back side of the machine, which is activated simply by inserting the vacuum hose. Other new features include the large lockable cable hook, an additional blower hose, and an easily removable filter cartridge which upgrades the machine's fine dust collection class to EPA12.





The KETOS N 81/2 K is equipped with an easily removable filter cartridge on



(elbow-bend hose) for the convenient emptying of the container.



The hose is electrically conductive and electric charge via the grounded body.

| TECHNICAL DATA | |
|------------------------|---------------------|
| Voltage | 220-240 V / 50 H |
| Max. power | 2600 W |
| Number of turbines | 2 |
| Sound pressure level | 76 dB(A) |
| Max. suction | 300 mbar |
| Volume flow rate | 2 x 70 litres / sec |
| Container material | plastic |
| Container volume | 80 litres (gross) |
| Length of power cord | 15 m |
| Length of hose | 3 m |
| Diametre of hose | 38 mm |
| Diametre of tubes | 38 mm |
| Weight | 20,6 kg |
| Dimensions (L x W x H) | 62 x 45 x 98 cm |
| | |



you choose between Economy and Turbo settings.



the exhaust side, upgradable to EPA12.



Waste-water release hose



EPA12 fine dust filter cartridge

 Extremely high performance Economy and Turbo power settings Low noise generation, only 76 db (A)

Emptying through crimped hose

Cyclone Water Separation System

• Unique, lockable cable hook

• Performance regulation

rubber-coated wheels

of device

cessed air.

stainless steel

Robust undercarriage, metal swivel casters and

· Container, push bar and vacuum tube made of

Systematically-separated cool and processed air

Complete storage of all accessories on the backside

complete accessory storage on the back of machine

Through the swirling motion at the intake, spray wa-

ter is segregated upon contact with the container wall.

Additional filter materials are no longer needed. The dependable floating deactivator reacts automatically

to high foam build-up. Cool air vents located on the sides ensure the absolute separation of fresh and pro-

The Illustration shows the patented water separation system



Standard: zyklon unit Item No. 109.057

112.002

KETOS N81/2K

2 x 0,5 m suction tubes stainless steel ø 38 mm,

3 m suction hose, crevice nozzle and furniture nozzle, wet floor nozzle 450 mm, dry floor nozzle 450 mm, EPA12 fine dust filter cartridge, fleece filter bag, zyklon unit, 10 m power cord, black

| ۰ | • | ٠ | ٠ | • | • | ٠ | • | • | ٠ | • | • | ٠ | • | • |
|---|---|---|---|---|---|----|---|---|---|---|---|---|---|---|
| c | | г | ۸ | N | Г | ١. | ٨ | D | Т | ١ | L | , | 1 | |

| Suction tubes stainless steel (1 piece) | 102.018 |
|---|---------|
| 3 m suction hose complete | 102.013 |
| Wet floor nozzle 450 mm | 102.118 |
| Dry floor nozzle 450 mm | 102.119 |
| Crevice nozzle | 102.016 |
| Furniture nozzle | 102.017 |
| Zyklon unit | 109.057 |
| EPA12 fine dust filter cartridge | 109.058 |
| 10 m power cord, black | 112.135 |
| ACCESSORIES: | |
| ΓΙ | 100 001 |

| rieece liller bag (5 pieces) | 102.031 |
|---|---------|
| EPA12 Filter cartridge | 112.101 |
| Metal floor nozzle 450 mm 450 mm | 102.051 |
| Combi nozzle 307mm | 109.084 |
| Suction hose complete, 15 m | 102.032 |
| Suction hose, antistatic, 3m | 102.116 |
| Brush strip set 450 mm for item no. 102.119 | 102.114 |
| Rubber strip set 450 mm for item no.102.118 | 102.115 |
| | |





Switch on the face of the machine lets





3 m antistatic suction hose. ensures optimum discharge of any Item no. 102.116.