



SPECIFICATIONS			
	P24 SC	P24 DC	P24 CC RGBW
LUMENS	10000	10000	7000
WATTAGE (MAX)	120	120	120
No. OF LEDs	24	24	24
I @ 12V	10	10	10
I @ 24V	5	5	5
BEAM ANGLE	60 DEG FWHM	60 DEG FWHM	60 DEG FWHM
LIGHT DIA	130mm (5.12")	130mm (5.12")	130mm (5.12")
LIGHT LENGTH	38.5mm (1.52")	38.5mm (1.52")	38.5mm (1.52")
LIGHT HEAD HEIGHT	18.5mm (0.73")	18.5mm (0.73")	18.5mm (0.73")
MOUNTING HOLES PCD	114mm (4.42")	114mm (4.42")	114mm (4.42")
HULL CUTOFF DIA	18mm (0.71")	18mm (0.71")	18mm (0.71")
LIGHT APERTURE	80mm (3.15")	80mm (3.15")	80mm (3.15")
WEIGHT	550gm	550gm	550gm
LENS	3mm HIGH IMPACT POLYMER WITH ANTI-STICK COATING	3mm HIGH IMPACT POLYMER WITH ANTI-STICK COATING	3mm HIGH IMPACT POLYMER WITH ANTI-STICK COATING

Bluefin LED
Underwater Lighting

© 2014 Square Rig Ltd. THIS DOCUMENT MUST NOT BE REPRODUCED IN WHOLE OR IN PART AND MUST NOT BE USED OR DISCLOSED WITHOUT THE WRITTEN AUTHORISATION OF COASTLINE LED. NO DEVIATION FROM THIS DRAWING IS PERMISSIBLE WITHOUT WRITTEN AUTHORISATION FROM COASTLINE LED.

SHEET: 1 OF 1 SCALE: 1:1 @ A3 THIRD ANGLE PROJECTION

DESCRIPTION: **P24 SERIES HIGH POWER SURFACE MOUNT LIGHT**

MATERIAL: MARINE AB2 BRONZE & POLYMER LENS

FINISH: SEE PART DRAWINGS

DRAWING No: **GAA-0142 Iss A00A** ISSUE: **A00** REV: **B** STATUS: