SPECIFICATIONS		
	ORCA O20 SC	ORCA O48 CC
LUMENS	13000	12000
WATTAGE (MAX)	122	155
No. OF LEDs	20	48
I @ 12V	N/A	N/A
I @ 24V	5.1	6.5
BEAM ANGLE	65 DEG FWHM	65 DEG FWHM
LIGHT DIA	140mm (5.5")	140mm (5.5")
LIGHT LENGTH	72.5mm (2.85")	72.5mm (2.85")
LIGHT HEAD HEIGHT	32mm (1.26")	32mm (1.26")
MOUNTING HOLES PCD	130mm (5.12")	130mm (5.12")
HULL CUTOUT DIA	30mm (1.18")	30mm (1.18")
LIGHT APERTURE	70mm (2.76")	70mm (2.76")
WEIGHT	2.3kg	2.3kg
LENS	8mm BOROSILICATE WITH ANTI-STICK COATING	8mm BOROSILICATE WITH ANTI-STICK COATING





SCALE: **1:1** @ A3

THIRD ANGLE PROJECTION

Bluefin LED
Underwater Lighting

© 2014 Square Rig Ltd THIS DOCUMENT MUST NOT BE REPRODUCED IN WHOLE OR IN PART AND MUST NOT BE USED OR DISCLOSED WITHOUT THE WRITTEN AUTHORISATION OF COASTLINE LED. NO DEVIATION FROM THIS DRAWING IS PERMISSABLE WITHOUT WRITTEN AUTHORISATION FROM COASTLINE LED.

:

DESCRIPTION: **ORCA OR20 / OR48CC SM**

MATERIAL: **MARINE AB2 BRONZE & GLASS LENS**

FINISH: SEE PART DRAWINGS

DRAWING No:	ISSUE:	REV:	STATUS:
GAA-0140 Iss C00C	**C00**	**C**	